



TECHNICAL DATA SHEET

Product	P 60G
Gruppo✓ Group	Plastificati Flexible
Categoria✓ Categorie	Stampaggio Articoli Tecnici Technical Articles Injection Moulding
Emissione: 1 del 04/2017 Revisione: 2 del 10/2020 Stato: Released	

TECHNICAL INFORMATION	TESTING METHOD	UNIT OF MEASURE	VALUE
Peso Specifico Specific Weight	ISO 1183-1	g/cm ³	1,260
Durezza Hardness	ISO 868	Shore A	61(PV) - 67(PI)
Carico di Rottura Tensile Strength	ISO 527	N/mm ²	10,5
Allungamento a Rottura Elongation at Break	ISO 527	%	320
Temp. di Irrig. a Torsione Cold Flex	ISO 458	°C	- 45
Stabilità Termica Heat Stability	CEI 20-34/3-2	Minutes	
Applicazioni	Compound stampaggio articoli tecnici (con materiale da riciclo). Esente DEHP. Conforme alla direttiva 2015/863/EU (RoHS III).		
Note	Le caratteristiche tecniche sopra riportate derivano da nostre analisi di laboratorio su campioni rappresentativi e sono da considerarsi valori medi tipici misurati sul prodotto e non possono essere usati come valori di specifica. Analisi eseguite su prodotto naturale non colorato.		
Applications	Compound for technical articles injection moulding (with recycle material). DEHP free. It is in compliance with directive 2015/863/EU (RoHS III).		
Notes	The above mentioned technical characteristics come from our laboratory tests done on representative samples. They have to be considered as average typical values measured on the product and can not be used as technical specification values. Analyses referred to natural material without pigments.		